

Globalstar Tri-Mode Satellite Phone

Smaller than most cordless phones, the Globalstar handheld GSP1600 satellite phone gives you crystal-clear digital satellite voice connections, connects to cellular systems where available, and provides real-world internet and e-mail access with the optional Globalstar data kit. A full range of optional accessories including vehicle kits or fixed site units help customize a solution to keep you in contact and in control. Whether you are at remote job sites, off-road, or offshore, the Globalstar handheld phone connects you to the people and information that you need most.

INCLUDES:

- Lithium Ion Battery
- Wall Charger
- User's Manual

FEATURES:

- Superior CDMA digital satellite quality
- 9600 Kbps CDMA Packet Data
- Convenient dialing: The only satellite phone with standard US dialing. Also supports all standard dial tone, dial procedure, and call progress touch-tones.
- Unparalleled Reliability: Path Diversity™ means each Globalstar call connects with at least 2 and up to 4 satellites per call for maximum quality and reliability.
- Compatibility with existing AMPS and CDMA 800 MHz cellular networks.
- Intuitive Display: Four-line, 48-character display shows battery level, voicemail status, short messages received and satellite signal quality.

SPECIFICATIONS:

- Dimensions: 7"(H) x 2.3"(W) x 1.9"(D)
177(H) x 57(W) x 48(D) mm
- Weight: 13 ounces (370 grams)
- **Battery time Globalstar**
 - 3.75 hour talk time
 - 19 hours standby
- **Battery time CDMA:**
 - 4.5 hours talk time
 - 72 hours standby
- **Battery time AMPS:**
 - 2.5 hours talk time
 - 14 hours standby
- **Display:** 4 lines of 12 characters
+ 1 line of icons
- Power source (battery), Polymer Lithium Ion battery
- Radio Frequency Power Output
 - Globalstar CDMA digital satellite mode: 400 mW maximum (+26 dBm)
 - CDMA Digital Cellular mode: 200 mW maximum
 - AMPS analog cellular mode: 600 mW maximum
- Frequency Range
 - Globalstar Reverse Link: 1610.73 to 1625.49 MHz
 - Globalstar Forward Link: 2484.39 to 249.15 MHz
 - Cellular Reverse Link: 824.01 to 848.97 MHz
 - Cellular Forward Link: 869.01 to 893.97 MHz
- Vocoder
 - Globalstar CDMA Digital Satellite Mode: 8k variable rate vocoder
 - CDMA Digital Cellular Mode: 13k variable rate vocoder

